



# 100 Celebrating YEARS

## AUSTRALIAN OWNED AND TRUSTED SINCE 1926



# HEAVY DUTY BEARING GREASE

Last updated: 25/09/2025 11:58 am

PRODUCT CODE	PACK SIZE	CARTON QTY
HDBG00045	450g	6
HDBG020	20Kg	
HDBG180	180Kg	

### PRODUCT BENEFITS

**Heavy Duty Bearing Grease** is an NLGI No 2, heavy duty, purple coloured, high temperature all-purpose, extreme pressure (EP) grease manufactured from high quality base oils and a lithium complex soap thickener. It is formulated for excellent load carrying ability, outstanding resistance to water washout and increased tackiness. It utilises a special borate additive system for effective extreme pressure performance and anti-wear protection.

### APPLICATION

**Heavy Duty Bearing Grease** is designed for use in industrial and automotive applications such as rolling element bearings, plain bearings, medium speed anti-friction bearings, steel mills, mining and ore crushing plants, general plant lubrication and in agricultural and construction equipment.

**Heavy Duty Bearing Grease** is suitable for use in wheel bearings in vehicles fitted with disc or drum brakes.

**Heavy Duty Bearing Grease** is suitable for use in all general chassis grease applications in automotive and industrial service, including in cars, 4WDs, trucks and buses.

### PRODUCT BENEFITS

- Excellent extreme pressure performance
- Protection against shock loadings
- Outstanding resistance to water wash out
- Protects against rust and corrosion, even in salt water
- Long service life
- Lead and chlorine free
- Good pumpability
- Contains tackifiers to help grease stay in place

### PRODUCT PERFORMANCE LEVELS

- DIN 51502: KP2R-30
- ISO 6743: ISO-L-XCFHB2
- NLGI 2
- Volvo 97720 (level)

### TYPICAL DATA

Colour	Purple
NLGI Grade	2
Soap Type	Lithium Complex
Density at 15°C, kg/L	0.9
Base Oil Viscosity, ISO	220
Operating Temperature Range °C	-30°C to +180°C
Appearance	Smooth / Tacky
Drop Point, °C	275
4-ball Weld Load, kg	620
Maximum Temperature, Intermittent use, °C	200

