



# HPR

## HPR Diesel 5

### Semi Synthetic 5W-40 Engine Oil

Issue: March 2017

Product Code	Pack Size	Ctn / Qty
HPRD5001	1 Litre	6
HPRD5005	5 Litre	4
HPRD5010	10 Litre	1
HPRD5020	20 Litre	1
HPRD5060	60 Litre	1
HPRD5205	205 Litre	1
HPRD51000	1000 Litre	1

### Product Description

**HPR Diesel 5** is a premium high performance semi synthetic SAE 5W-40, non-friction modified engine oil. Contains a **DOUBLE LAYER** of engine wear protection with **FULL ZINC** and Penrite's advanced **EXTRA TEN** technology. It contains a combination of high technology additives, including increased dispersant levels and low shear viscosity modifiers. It protects against corrosion, oil oxidation and sludge under all operating conditions.

**HPR Diesel 5** meets the requirements of API CI-4 PLUS/SL and ACEA A3/B4/E7 as well as many manufacturers' requirements

### Application

**HPR Diesel 5** is designed for use in modern 4, 6 & 8+ cylinder multi cam, multi valve (Including VVT), naturally aspirated, supercharged, turbocharged common rail & direct injection engines. It is also suitable for diesel engines that are equipped with hydraulically actuated injector units.

**HPR Diesel 5** can be used where SAE 5W-30, SAE 5W-40, SAE 10W-30 & SAE 10W-40 grade oils were originally recommended by the manufacturer. It is suitable for use where fuel economy specifications ACEA A1/B1, A5/B5 and Global DLD-2 are specified in the owner's hand book. It is also suitable for use where Ford specification M2C913-A/B/C is required for out of warranty service.

**HPR Diesel 5** is **NOT** recommended for vehicles fitted with a DPF (Diesel Particulate Filter) that require a low SAPS engine oil. Penrite **Enviro+** engine oils should be used on vehicles fitted with a DPF. We recommend checking the recommendation guide for the correct grade and specification.

### Vehicle & Fuel Types

**HPR Diesel 5** is suitable for use in diesel engines in passenger cars, motorcycles, 4WD's, light & heavy duty commercial engines in trucks, tractors, agricultural & earthmoving equipment as well as industrial equipment such as fork lifts & stationary engines. It is suitable for use with Diesel & Petrol/E10/LPG (Dual Fuel). It is also suitable for use in petrol and LPG engines as a mixed fleet oil and can be used in motorcycles with wet clutches.

### Extra Ten Technology

**HPR Diesel 5** features Penrite's Extra Ten technology that provides better wear protection, oil pressure and reduced oil consumption at operating temperature. It can be used where SAE 5W-30, SAE 5W-40, SAE 10W-30 & SAE 10W-40 grade oils were originally recommended by the manufacturer.



# PENRITE



**PENRITE OIL COMPANY PTY LTD**, 88 Lewis Road, Wantirna South  
 Victoria AUSTRALIA 3152, ABN 25 005 001 525  
 Enquiries: Phone 1300-PENRITE (1300 736 748)  
 Fax: 1800-PENRITE (1800 736 748)  
 International: Phone: 61 3 9801 0877, Fax: 61 3 9801 0977  
 New Zealand Ph: 0800 533 698, Fax: 0508 736 748  
 United Kingdom and EU Ph: +44 (0) 1594 562357, Fax: +44 (0) 1594 564234  
 Website: www.penriteoil.com, Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN  
 FAMILY OWNED  
 SINCE 1926**



