



# PENRITE



85% REDUCTION IN LANDFILL WASTE

## MC4-ST 10W-40 (PAO ESTER)

Last updated: 16/04/2018 9:37 am

PRODUCT CODE	PACK SIZE	CARTON QTY
MC410W40001	1L	6
MC410W400025	2.5L	4
MC410W40004	4L	4
MC410W40020	20L	



### PRODUCT BENEFITS

**MC4-ST 10W-40** is the superior performance premium engine oil with 100% PAO & Ester, full synthetic base oils combined with the latest additive technology including **\*FULL ZINC +** (exceeding 1800+ ppm levels) for maximum engine, gearbox & clutch protection against wear, corrosion, oil oxidation, piston deposits and sludge under all conditions. It exceeds the requirements of API SN/CF and JASO MA.

### FACTORY RACING

Penrite 10 Tenths Racing products are used by **Factory Race Teams** to provide the ultimate in performance and protection. To visit our Factory Racing Partners and Penrite Brand Ambassadors [Click Here](#)

### APPLICATION

**MC4-ST 10W-40** is designed for use in most modern four stroke road & sports bikes, dirt & enduro bikes, ATVs/Quad bikes and 4 stroke scooters that require a full synthetic engine oil. It is also equally suitable for use in transmissions with wet clutch systems where engine & gearbox oils are combined. It has optimum clutch slip prevention in these systems being compliant with JASO MA as is suitable for use where JASO MA1 and JASO MA2 is specified.

**MC4-ST 10W-40** can be used where semi synthetic or other types of oils are specified by the manufacturer including where SAE 10W-30 & SAE 10W-40 grade oils are recommended such as in Aprilia, BMW, Cagiva, Can-Am, Ducati, Hyosung, Kawasaki, Suzuki, Triumph, Yamaha and more.

**MC4-ST 10W-40** contains **100% PAO and Ester** base oils that provide superior oil film strength, heat resistance and oil shear protection combined with a **SHEAR FREE** formulation that eliminates viscosity loss and maintains oil pressure during extreme engine operating conditions ensuring the ultimate in protection for your engine.

**MC4-ST 10W-40** is also suitable for use in other four stroke engines such as stationary engines & generators or other vehicles that require this grade and specification of engine oil and can be used with petrol, racing & other conventional fuels.

**\*Full Zinc +** = Zinc level + Boron level combined as a total anti-wear package

### PRODUCT BENEFITS

- **PREMIUM 100% PAO** and **ESTER** base oils for maximum heat resistance and high performance
- **\*FULL ZINC+** additive pack for ultimate wear protection
- **SHEAR FREE** formulation eliminates viscosity loss
- **LATEST** oil technology for less wear, sludge & piston deposits
- **MAXIMUM** power and acceleration
- **FACTORY PROVEN** by competition race teams
- Backward compatible and suitable for use with SM, SL, SJ, SH & SG oils
- Trusted protection for performance engines
- Suitable for use with wet clutch systems (JASO MA, JASO MA1 and JASO MA2)
- Extends engine life by reducing high temperature engine deposits

**\*Full Zinc +** = Zinc level + Boron level combined as a total anti-wear package

### INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- API SJ/CF
- API SL/CF
- API SM/CF
- API SN/CF
- JASO MA



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## **TYPICAL DATA**

Density at 15°C, kg/L	0.861
Viscosity, Kinematic, cSt at 40°C	91
Viscosity, Kinematic, cSt at 100°C	14.4
Viscosity Index	164
Cold Cranking Viscosity, cP at -25°C	6177
Zinc, Mass %	0.124
Boron, Mass %	0.063
Phosphorus, Mass %	0.112
Sulphated Ash, Mass %	1.2
Base Number	9.8