

Material Safety Data Sheet

CS: 1.4.22

Page: 1 of 4

Infosafe No™ LPUOA Issue Date : June 2008 ISSUED by PENRITEO CS: 1.4.22

Product Name : **HI-PER TWO STROKE ENGINE OIL**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name HI-PER TWO STROKE ENGINE OIL
Product Code SEHPTS
Company Name PENRITE OIL COMPANY P/L (ABN 25005 001 525)
Address 88 Lewis Road Wantirna South
Victoria 3152 Australia
Emergency Tel. 03 9801 0877 B.H
Telephone/Fax Number Tel: 03 9801 0877
Recommended Use Two stroke petrol engine oil.

2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS SUBSTANCE.
NON-DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

Risk Phrase(s) R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness and cracking.

Safety Phrase(s) S2 Keep out of reach of children.
S24/25 Avoid contact with skin and eyes.
S37/39 Wear suitable gloves and eye/face protection.
S61 Avoid release to the environment. Refer to special instructions/safety data sheet.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Ingredients determined not to be hazardous	Not required	60-100 %
	Distillates, petroleum, hydrotreated light	64742-47-8	10-30 %

4. FIRST AID MEASURES

Inhalation If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.

Ingestion Do NOT induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.

Skin Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek medical attention.

Eye If in eyes wash out immediately with water. Continue flushing for several minutes until all contaminants are washed off completely. Seek medical attention.

First Aid Facilities Eye wash and normal washroom facilities.

Advice to Doctor Treat symptomatically.

Other Information For advice, contact the Poisons Information Centre Australia on 131 126.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media Use carbon dioxide, dry chemical, foam or water mist.

Material Safety Data Sheet

CS: 1.4.22

Page: 2 of 4

Infosafe No™ LPUOA	Issue Date : June 2008	ISSUED by PENRITEO	CS: 1.4.22
--------------------	------------------------	--------------------	------------

Product Name : **HI-PER TWO STROKE ENGINE OIL**

Hazards from Combustion Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Products Specific Hazards Combustible liquid. This product will burn if exposed to fire.

Precautions in connection with Fire Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for the subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling Wear appropriate protective equipment to prevent inhalation and eye exposure. Use in designated areas with adequate ventilation. Avoid breathing in spray, mist or vapours. Keep containers closed when not in use. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. Practice good personal hygiene, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.

Conditions for Safe Storage Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Storage Regulations Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purposes of storage and handling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m³. As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Biological Limit Values No biological limit allocated.

Engineering Controls Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.

Respiratory Protection Normally not required, however if mists or vapours are generated and ventilation is inadequate, particularly in enclosed areas then an approved respirator with a replaceable organic vapour/mist filter is recommended. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should

Material Safety Data Sheet

CS: 1.4.22

Page: 3 of 4

Infosafe No™ LPUOA Issue Date : June 2008 ISSUED by PENRITEO CS: 1.4.22

Product Name : **HI-PER TWO STROKE ENGINE OIL**

Hand Protection conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Wear gloves of impervious material such as neoprene or nitrile rubber. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Orange liquid
Odour	Not available
Melting Point	Not available
Boiling Point	Not available
Solubility in Water	Not available
pH Value	Not applicable
Vapour Pressure	Not available
Vapour Density (Air=1)	Not available
Viscosity	9.0 cSt at 100°C 57 cSt at 40°
Pour Point	-18°C
Density	0.862 at 15°C
Flash Point	97°C
Flammability	Combustible liquid
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, direct sunlight, open flames or other sources of ignition.
Incompatible Materials	Strong oxidising agents.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	No toxicology data available for this product.
Inhalation	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Ingestion	Harmful: may cause lung damage if swallowed. Ingestion of this product may irritate the gastric tract causing nausea and vomiting. Ingestion and subsequent vomiting may result in aspiration of liquid into the lungs, causing chemical pneumonia leading to lung damage.
Skin	May be irritating to skin, may cause redness, itching and irritation. Repeated

Material Safety Data Sheet

CS: 1.4.22

Page: 4 of 4

Infosafe No™ LPUOA	Issue Date : June 2008	ISSUED by PENRITEO	CS: 1.4.22
--------------------	------------------------	--------------------	------------

Product Name : **HI-PER TWO STROKE ENGINE OIL**

Eye	exposure may cause skin dryness and cracking. On eye contact this product may cause tearing, stinging, blurred vision, and redness.
------------	--

12. ECOLOGICAL INFORMATION

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Persistence / Degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Environ. Protection	Do not allow product to enter drains, waterways or sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.
--------------------------------	--

14. TRANSPORT INFORMATION

Transport Information	Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
------------------------------	---

15. REGULATORY INFORMATION

Regulatory Information	Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
Poisons Schedule	Not Scheduled
Hazard Category	Harmful, Dangerous for the environment

16. OTHER INFORMATION

Date of preparation or last revision of MSDS	MSDS reviewed: June 2008. Supersedes: June 2006.
Contact Person/Point	TITLE: Technical and Marketing Director TELEPHONE NUMBER: 03 9801 0877 B.H ...End Of MSDS...

© Copyright ACOHS Pty Ltd
Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.
Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed on this site is the intellectual property of Acohs Pty Ltd.
Copying of any MSDS displayed on this site is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed on this site cannot be