

# Material Safety Data Sheet

CS: 1.4.22

Page: 1 of 4

Infosafe No™ LPXOT Issue Date :October 2008 ISSUED by PENRITEO CS: 1.4.22

Product Name : PRO 15 PLUS

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name** PRO 15 PLUS  
**Product Code** PRO15PLUS  
**Company Name** PENRITE OIL COMPANY P/L (ABN 25005 001 525)  
**Address** 88 Lewis Road Wantirna South  
Victoria 3152 Australia  
**Emergency Tel.** 03 9801 0877 B.H  
**Telephone/Fax Number** Tel: 03 9801 0877  
**Recommended Use** Petrol engine oil

## 2. HAZARDS IDENTIFICATION

**Hazard Classification** NON-HAZARDOUS SUBSTANCE.  
NON-DANGEROUS GOODS.  
Hazard classification according to the criteria of NOHSC.  
Dangerous goods classification according to the Australia Dangerous Goods Code.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Ingredients</b>	<b>Name</b>	<b>CAS</b>	<b>Proportion</b>
	Distillates (petroleum), Solvent Dewaxed, Heavy Paraffinic Base Oil - Unspecified Ingredients	64742-65-0	30-60 %  10-<30 % Balance
<b>Other Information</b>	Note: Ingredients that have been assigned Note L of the Worksafe designated List of Hazardous Substances, have been tested in accordance with IP 346. This product contains less than 3% polyaromatics and is therefore non hazardous.		

## 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.  
**Ingestion** Do NOT induce vomiting. Wash out mouth with water. If symptoms develop seek medical attention.  
**Skin** Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek medical attention.  
**Eye** If in eyes, hold eyelids apart and flush the eyes immediately with running water. Continue flushing for several minutes until all contaminants are washed off completely. Seek medical attention.  
**First Aid Facilities** Eye wash and normal washroom facilities.  
**Advice to Doctor** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media** Carbon dioxide, dry chemical, foam and water fog.  
**Hazards from Combustion Products Specific Hazards** Under fire conditions this product may emit toxic and/or irritating fumes including aldehydes, oxides of sulphur and nitrogen, hydrogen sulfide, metallic oxides, carbon monoxide and carbon dioxide.  
Combustible liquid. This product will burn if exposed to fire.  
**Precautions in connection with Fire** Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

# Material Safety Data Sheet

CS: 1.4.22

Page: 2 of 4

Infosafe No™ LPXOT Issue Date :October 2008 ISSUED by PENRITEO CS: 1.4.22

Product Name : PRO 15 PLUS

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures** Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Spillage may be slippery. Pump into suitable containers or place inert, non-combustible absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for the subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.

## 7. HANDLING AND STORAGE

**Precautions for Safe Handling** Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with large quantities, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. Practice good personal hygiene, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.

**Conditions for Safe Storage** Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do not pressurise, cut, drill, grind, weld or perform similar operations on or near containers. Do not remove labels. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

**Storage Regulations** Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purposes of storage and handling, in accordance with the requirements of AS1940.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**National Exposure Standards** No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m<sup>3</sup>. As with all chemicals, exposure should be kept to the lowest possible levels.

The National Occupational Health and Safety Commission (NOHSC) exposure standards for hydrogen sulfide (decomposition product) is

	TWA		STEL	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Hydrogen sulfide	10	14	15	21

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

**Biological Limit Values** No biological limit allocated.

**Engineering Controls** Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.

**Respiratory Protection** If mists or vapours are generated and ventilation is inadequate, particularly in enclosed areas then an approved respirator with a replaceable organic vapour/mist filter is recommended. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of

# Material Safety Data Sheet

CS: 1.4.22

Page: 3 of 4

Infosafe No™ LPXOT	Issue Date :October 2008	ISSUED by PENRITEO	CS: 1.4.22
--------------------	--------------------------	--------------------	------------

Product Name : **PRO 15 PLUS**

---

<b>Respiratory Protective Devices;</b> and AS/NZS 1716, Respiratory Protective Devices.
<b>Eye Protection</b> Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
<b>Hand Protection</b> Wear gloves of impervious material such as nitrile. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
<b>Body Protection</b> Wear appropriate clothing e.g. cotton overalls buttoned at neck and wrist and include chemical resistant apron where clothing is likely to be contaminated. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	Liquid
<b>Odour</b>	Characteristic odour
<b>Freezing Point</b>	Not available
<b>Boiling Point</b>	Not available
<b>Solubility in Water</b>	Insoluble
<b>pH Value</b>	Not applicable
<b>Vapour Pressure</b>	Not available
<b>Vapour Density (Air=1)</b>	Not available
<b>Viscosity</b>	18.8 cSt at 100°C 144 cSt at 40°C
<b>Density</b>	0.880 at 15°C
<b>Flash Point</b>	218°C
<b>Flammability</b>	Combustible liquid
<b>Flammable Limits - Lower</b>	Not available
<b>Flammable Limits - Upper</b>	Not available
<b>Other Information</b>	CCS Viscosity 5786 cP at -20°C

---

## 10. STABILITY AND REACTIVITY

---

<b>Chemical Stability</b>	Stable under normal conditions of storage and handling.
<b>Conditions to Avoid</b>	Heat, direct sunlight, open flames or other sources of ignition.
<b>Incompatible Materials</b>	Strong oxidising agents.
<b>Hazardous Decomposition Products</b>	Thermal decomposition may result in the release of toxic and/or irritating fumes including aldehydes, oxides of sulphur and nitrogen, hydrogen sulfide, metallic oxides, carbon monoxide and carbon dioxide.
<b>Hazardous Polymerization</b>	Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

<b>Toxicology Information</b>	No toxicology data available for this specific product. However, for the base oil, the following data applies: LD50 (Oral, rat) : > 2000 mg/kg LD50 (Dermal, rabbit) : > 2000 mg/kg
-------------------------------	---

# Material Safety Data Sheet

CS: 1.4.22

Page: 4 of 4

Infosafe No™ LPXOT	Issue Date :October 2008	ISSUED by PENRITEO	CS: 1.4.22
--------------------	--------------------------	--------------------	------------

Product Name : **PRO 15 PLUS**

---

<b>Inhalation</b>	LC50 (Inhalation, rat) : > 5000 mg/m3 Repeated or prolonged inhalation of product vapours may cause irritation of the nose, throat and respiratory system, or other pulmonary effects.
<b>Ingestion</b>	Ingestion of this product may irritate the gastric tract causing nausea, diarrhoea and vomiting.
<b>Skin</b>	Repeated or prolonged contact with skin may dry and defat the skin, and cause irritation and dermatitis.High-pressure injection under skin may cause serious damage.
<b>Eye</b>	May cause eye irritation, tearing, stinging, blurred vision, and redness.
<b>Chronic Effects</b>	Repeated or prolonged contact may result in skin irritation leading to dermatitis.

---

## 12. ECOLOGICAL INFORMATION

---

<b>Ecotoxicity</b>	No data is available for this material. However, oil spills can smother and suffocate aquatic life by preventing passage of oxygen into water. Oil contamination can also foul and smother birds and marine animals.
<b>Persistence / Degradability</b>	Not available
<b>Mobility</b>	Insoluble in water. Expected to float.
<b>Bioaccumulative Potential</b>	Not available
<b>Environ. Protection</b>	Do not allow product to enter drains, waterways or sewers.

---

## 13. DISPOSAL CONSIDERATIONS

---

<b>Disposal Considerations</b>	The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.
--------------------------------	--

---

## 14. TRANSPORT INFORMATION

---

<b>Transport Information</b>	Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
------------------------------	---

---

## 15. REGULATORY INFORMATION

---

<b>Regulatory Information</b>	Not Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
<b>Poisons Schedule</b>	Not Scheduled

---

## 16. OTHER INFORMATION

---

<b>Date of preparation or last revision of MSDS</b>	MSDS Prepared: October 2008
<b>Contact Person/Point</b>	TITLE: Technical and Marketing Director TELEPHONE NUMBER: 03 9801 0877 B.H ...End Of MSDS...

© Copyright ACOHS Pty Ltd  
Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.  
Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.  
The compilation of MSDS's displayed on this site is the intellectual property of Acohs Pty Ltd.  
Copying of any MSDS displayed on this site is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed on this site cannot be