

Material Safety Data Sheet

Page: 1 of 4

Infosafe No. LPWBK Issue Date : March 2007 ISSUED by PENRITEO

Product Name : **TRANSOIL 90**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name TRANSOIL 90
Product Code T90
Company Name PENRITE OIL COMPANY P/L (ABN 25005 001 525)
Address 88 Lewis Road Wantirna South
Victoria 3152 Australia
Emergency Tel. 03 9801 0877 B.H
Telephone/Fax Number Tel: 03 9801 0877
Recommended Use Gear oil

2. HAZARDS IDENTIFICATION

Hazard Classification NON-HAZARDOUS SUBSTANCE.
NON-DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Information on Composition Petroleum derived base oils and proprietary additives.

| Ingredients | Name | CAS | Proportion |
|--------------------|---|------------|-------------------|
| | Residual oils (petroleum), solvent dewaxed | 64742-62-7 | 30-60 % |
| | Distillates (Petroleum), Solvent Dewaxed Heavy Paraffinic | 64742-65-0 | 30-60 % |
| | Ingredients determined not to be hazardous | | Balance |

4. FIRST AID MEASURES

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.
Ingestion Do NOT induce vomiting. Wash out mouth with water. If symptoms develop seek medical attention.
Skin Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. If symptoms develop seek medical attention.
Eye If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist seek medical attention.
First Aid Facilities Eye wash and normal washroom facilities.
Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media CO2, Dry Chemical, Foam and Water Fog.
Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Specific Hazards Combustible liquid. This product will burn if exposed to fire.
Precautions in connection with Fire Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe

Material Safety Data Sheet

Infosafe No. LPWBK Issue Date : March 2007 ISSUED by PENRITEO

Product Name : TRANSOIL 90

to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Precautions for Safe Handling Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. Wear appropriate protection. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for Safe Storage Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m³. As with all chemicals, exposure should be kept to the lowest possible levels.

Biological Limit Values No biological limit allocated.

Engineering Controls Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.

Respiratory Protection If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

Eye Protection Safety glasses with side shields or chemical goggles as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection Wear laminated film, nitrile or other suitable gloves conforming to AS/NZS 2161: Occupational protective gloves.

Body Protection Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Brown oil

Odour Mineral oil odour

Melting Point -12°C

Material Safety Data Sheet

| | | | |
|--------------|-------|-------------------------|--------------------|
| Infosafe No. | LPWBK | Issue Date : March 2007 | ISSUED by PENRITEO |
|--------------|-------|-------------------------|--------------------|

Product Name : **TRANSOIL 90**

| | |
|----------------------------------|---|
| Boiling Point | >350°C |
| Solubility in Water | Insoluble |
| Specific Gravity | 0.899 @15°C |
| pH Value | Not applicable |
| Vapour Pressure | Not available |
| Vapour Density (Air=1) | Not available |
| Viscosity | 18.4 cSt @100°C 210 cSt @40°C |
| Pour Point | -12°C |
| Flash Point | 260°C |
| Flammability | Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purposes of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well ventilated area away from naked flames, sparks and other sources of ignition. |
| Auto-Ignition Temperature | Not available |
| Flammable Limits - Lower | Not available |
| Flammable Limits - Upper | Not available |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical Stability | Stable under normal conditions. |
| Conditions to Avoid | Heat, direct sunlight, open flames or other sources of ignition. |
| Incompatible Materials | Strong oxidising agents. |
| Hazardous Decomposition Products | Oxides of carbon, aldehydes and ketones. |
| Hazardous Reactions | Hazardous polymerisation will not occur. |

11. TOXICOLOGICAL INFORMATION

| | |
|-------------------------------|--|
| Toxicology Information | No toxicology data available for this product. |
| Inhalation | Inhalation of product vapours may cause irritation of the nose, throat and respiratory system. |
| Ingestion | Ingestion of this product may irritate the gastric tract causing nausea and vomiting. |
| Skin | May cause redness, itching and irritation. |
| Eye | May cause eye irritation, tearing, stinging, blurred vision, and redness. |
| Chronic Effects | Prolonged or repeated skin contact may cause dermatitis due to defatting effect. |

12. ECOLOGICAL INFORMATION

| | |
|------------------------------------|--------------------------------|
| Ecotoxicity | Not available |
| Persistence / Degradability | Not available |
| Mobility | Not available |
| Environ. Protection | Avoid contaminating waterways. |

13. DISPOSAL CONSIDERATIONS

| | |
|--------------------------------|---|
| Disposal Considerations | Dispose of waste according to federal, EPA and state regulations. |
|--------------------------------|---|

14. TRANSPORT INFORMATION

Material Safety Data Sheet

Page: 4 of 4

| | | | |
|--------------|-------|-------------------------|--------------------|
| Infosafe No. | LPWBK | Issue Date : March 2007 | ISSUED by PENRITEO |
|--------------|-------|-------------------------|--------------------|

Product Name : **TRANSOIL 90**

Transport Information Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

Storage and Transport Not classified as dangerous.

15. REGULATORY INFORMATION

Poisons Schedule Not Scheduled

16. OTHER INFORMATION

Date of preparation or last revision of MSDS MSDS Created: March 2007

...End Of MSDS...