

Material Safety Data Sheet

Page: 1 of 4

Infosafe No. LPVG7 Issue Date : May 2006 ISSUED by PENRITEO

Product Name : UPPER CYLINDER AND LPG LUBRICANT

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name UPPER CYLINDER AND LPG LUBRICANT
Product Code UCL
Company Name PENRITE OIL COMPANY P/L (ABN 25005 001 525)
Address 88 Lewis Road Wantirna South
Victoria 3152 Australia
Emergency Tel. 03 9801 0877 B.H
Telephone/Fax Number Tel: 03 9801 0877
Recommended Use Petrol system additive.

2. HAZARDS IDENTIFICATION

Hazard Classification NON-HAZARDOUS SUBSTANCE.
NON-DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Ingredients determined not to be hazardous	Not required	100 %

4. FIRST AID MEASURES

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. If symptoms develop seek medical attention.
Ingestion Do NOT induce vomiting. Wash out mouth with water. If symptoms develop seek medical attention.
Skin Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.
Eye If contact with the eye(s) occurs, wash with copious amounts of water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. If symptoms persist seek medical attention.
First Aid Facilities Eye wash and normal washroom facilities.
Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media CO2, Dry Chemical, Foam and Water Fog.
Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Specific Hazards Combustible liquid. This product will burn if exposed to fire.
Hazchem Code None Allocated
Precautions in connection with Fire Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.

7. HANDLING AND STORAGE

Material Safety Data Sheet

Infosafe No.	LPVG7	Issue Date : May 2006	ISSUED by PENRITEO
Product Name :	UPPER CYLINDER AND LPG LUBRICANT		

Precautions for Safe Handling	Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with large quantities, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for Safe Storage	Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purposes of storage and handling. Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	No exposure standards have been established for this material, however, the TWA National Occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m ³ . As with all chemicals, exposure should be kept to the lowest possible levels.
Biological Limit Values	No biological limit allocated.
Engineering Controls	Provide sufficient ventilation to keep airborne levels below the exposure limit. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required. Refer to AS1940 - The storage and handling of flammable and combustible liquids and AS2430 - Explosive gas atmospheres for further information concerning ventilation requirements.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated. It is advisable that a local supplier of personal protective clothing is consulted regarding the choice of material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Oily liquid.
Odour	Mineral oil odour.
Melting Point	Not available.
Boiling Point	Not available.
Solubility in Water	Not available.
Specific Gravity	0.871 (15°C)

Material Safety Data Sheet

Page: 3 of 4

Infosafe No.	LPVG7	Issue Date : May 2006	ISSUED by PENRITEO
--------------	-------	-----------------------	--------------------

Product Name : **UPPER CYLINDER AND LPG LUBRICANT**

pH Value Not applicable.

Vapour Pressure Not available.

Vapour Density (Air=1) Not available.

Viscosity 22cSt (40°)

Flash Point <65°C

Auto-Ignition Temperature Not available.

Flammable Limits - Lower Not available.

Flammable Limits - Upper Not available.

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

Conditions to Avoid Heat, direct sunlight, open flames or other sources of ignition.

Incompatible Materials Strong oxidising agents.

Hazardous Decomposition Products Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Hazardous Reactions Hazardous polymerisation will not occur.

11. TOXICOLOGICAL INFORMATION

Inhalation Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Ingestion Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Skin May cause redness, itching and irritation.

Eye May cause eye irritation, tearing, stinging, blurred vision, and redness.

Chronic Effects Repeated or prolonged skin contact may lead to dermatitic effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity No data is available for this material.

Persistence / Degradability No data is available for this material.

Mobility No data is available for this material.

Environ. Protection Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations Dispose of waste according to federal, EPA and state regulations.

14. TRANSPORT INFORMATION

Transport Information Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

U.N. Number None Allocated

Proper Shipping Name None Allocated

DG Class None Allocated

Hazchem Code None Allocated

Packing Group None Allocated

15. REGULATORY INFORMATION

Poisons Schedule Not Scheduled

Material Safety Data Sheet

Page: 4 of 4

Infosafe No.	LPVG7	Issue Date : May 2006	ISSUED by PENRITEO
--------------	-------	-----------------------	--------------------

Product Name : **UPPER CYLINDER AND LPG LUBRICANT**

16. OTHER INFORMATION

Date of preparation MSDS created: May 2006.

**or last revision of
MSDS**

Contact Person/Point TITLE: Technical and Marketing Director
TELEPHONE NUMBER: 03 9801 0877 B.H
...End Of MSDS...