



Product Information

ATF TOP UP

Codes: ATFTU001

Issue: January 2010

Special purpose, heavier viscosity, automatic transmission fluid meeting the basic frictional and anti-wear requirements of DEXRON®-IIE.

Application

Used for the top up of all car and truck automatic transmissions including US, European and Japanese automatics.

Also suitable for all power steering units that specify automatic transmission fluids.

This product is not recommended for top up where the below products and their equivalents are specified:

ATF DX-VI

CVT Fluid V

Audi/Subaru CVT Fluid

Customer Benefits

- Compatible with a wide range of seal materials.
- Maximises equipment life by maintaining wear protection and oil film thickness.
- Excellent anti-foam characteristics.
- Suited for top up (up to a maximum of 20% by volume) of all automatic transmissions.
- Compatible with all DEXRON® type fluids

Industry Specifications

Penrite ATF Top Up meets the performance requirements of:

DEXRON®-IID/IIE
Allison C-4
ZF TE-ML11
Ford M2C-166H
Voith Diwa
Vickers 35VQ25

MERCON®-IV
MB 236.1
Ford ESR-M2C-163A
Ford M2C-138CJ
Denison T5D, P-46, HF-2
Sundstrand 22-213L

Typical Properties

Density at 15°C, kg/L	0.863
Viscosity, Kinematic, cSt	
at 40°C	55
at 100°C	9.3
Viscosity Index	152
Colour	Dark Red
Phosphorus, mass %	0.031
Boron, mass %	0.014

Environment, Health and Safety

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.
Issued January 2010