



## Product Information

# HPR GAS

**Codes:** HPRG001, HPRG005, HPRG010, HPRG020, HPRG060, HPRG205

**Issue:** January 2010

Premium mineral SAE 20W-60 engine oil, formulated with a unique combination of highly refined mineral oils, additives and viscosity modifiers to the highest standards to ensure protection against wear, corrosion, oil oxidation and sludge under tough Australian Conditions.

Penrite HPR Gas meets the requirements of API CG-4/SL and the European Standards ACEA A3/B4, as well as many manufacturers' specifications.

### Application

Designed for use in older LPG engines in cars, four wheel drives and light commercial vehicles (<3.5t gross vehicle mass).

Especially suited for older Holden and Ford LPG engines in severe taxi service.

Also suitable for passenger car diesel and petrol engines as a mixed fleet oil.

It is also suitable for four stroke motorcycles with integral clutches/transmissions and is our primary recommendation for post 1992 Harley Davidson motorcycle engines.

### Customer Benefits

- Greater engine protection at high operating temperatures compared to 15W-40 and 20W-50 LPG oils.
- High operating temperature viscosity helps to control oil consumption and maintain oil pressure under arduous conditions.
- Longer engine life by reducing formation of high temperature engine deposits.
- Resists severe nitration, resulting in longer bearing life.

### Industry Specifications

Penrite HPR Gas meets the performance requirements of:

API CG-4/SL	ACEA A3/B3/B4 (Europe)
Holden HN 2314	Ford WSE-M2C902-A3 VW 501.01

## Typical Properties

Density at 15°C, kg/L	0.887
Viscosity, Kinematic, cSt	
at 40°C	233
at 100°C	24.5
Viscosity Index	132
Viscosity, Cold Cranking @ -15 °C	8361
Zinc, mass %	0.122
Sulphated Ash, mass %	1.22
Base Number	9.4