



Product Information

HERITAGE LTM AND MTH

Codes: *HERLTM001, HERMTH001*

Issue: *January 2010*

Two monograde products manufactured from high quality mineral base oils and containing anti-wear, anti-rust and tackiness additives.

Application

Heritage LTM:

Heritage LTM is light to medium viscosity engine oil designed to meet the requirements of small engined veteran, Edwardian cars or 1, 2 and 4 cylinders, and motorcycles up to 500cc prior to 1920.

Many vehicles of pre WWI design which were fitted with rather primitive oiling systems such as drip feed lubricator systems, wick feed, and hand operated pumps. These require an engine oil that will readily flow when cold yet provide the necessary protection when hot. Also recommended for early forms of smaller capacity (less than 6hp) stationary engines and other early agricultural equipment fuelled by either petrol, kerosene (paraffin) or diesel.

Heritage MTH:

Heritage MTH is a medium to heavy viscosity engine oil designed to meet the requirements of medium to large veteran, Edwardian cars or 4, 6 and 8

cylinders, and motorcycles of 500cc capacity or over built prior to 1920.

For use in large capacity engine is vehicles fitted with trough or early forms of pressure fed systems, requiring a heavier grade of oil than Heritage LTM. Also recommended for early forms of larger capacity (over 6hp) stationary engines which may be subjected to constant unloaded running, or where a thinner grade oil would not provide the necessary protection at high ambient temperatures. May also be used in other forms of early agricultural equipment fuelled by either petrol, kerosene (paraffin) or diesel.

Customer Benefits

- Contains modern additives to provide corrosion protection (when vehicle not in use), water resistance (results of primitive water pump design leaking water into sump) and tenacity (clinging ability).

Industry Specifications

- Typical oil change intervals should not exceed 500 miles/800km or yearly, whichever comes first.

Typical Properties

Product	HERLTM	HERMTH
SAE Grade	30	50
Density at 15°C, kg/L	0.891	0.897
Viscosity, Kinematic, cSt		
at 40°C	100	220
at 100°C	11.3	19.7