



Product Information

HYDRAULIC JACK OIL

Codes: HJ00005

Issue: January 2010

Low zinc, premium quality ISO 46 hydraulic oil made from selected base stocks and an advanced anti-wear additive.

Application

Penrite Hydraulic Jack Oil is recommended for use in all types of hydraulic jacks and hoists.

It is also suitable for use in systems that use vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks, windmill gears) and hydraulic hoists and jacks. It may also be used in some types of reciprocating and piston compressors where this type of oil is called for.

Available only in a handy 500ml pack.

Customer Benefits

- Formulated to combat rust, oxidation, wear and foaming.
- Reduces sludge formation.
- Compatible with silver components.
- Provides good water separation.
- Compatible with other hydraulic oils.

Industry Specifications

Denison HF0, HF1, HF2
Cincinnati Milacron P-69 (HM)
DIN 51524 Part 2 (HLP Type)
US Steel 136, 127

Vickers I-286-S, M-2950-S

Typical Properties

Density at 15°C, kg/L	0.872
Viscosity, Kinematic, cSt	
at 40°C	44.6
at 100°C	6.8
Viscosity Index	98
Zinc, mass %	0.032

Penrite Oil Company Pty Ltd
ABN 25 005 001 525
Ph: 1300 PENRITE (1300 736 748)
Int: 61 3 980 1 0877
Email: penrite@penriteoil.com
www.penriteoil.com.au

Environment, Health and Safety

Information is available by request on this product in the Penrite Material Safety Data Sheet. Information in this sheet is based on the most current information available. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacture.
Issued January 2010