



Product Information

MB 15 SUSPENSION FLUID

Codes: MB15001, MB15205

Issue: January 2010

Penrite MB 15 is a light, high viscosity index, zinc free mineral oil meeting MB 343.0 designed for some self levelling suspension units.

APPLICATION

For use in Mercedes-Benz self-levelling suspension units that specify this type of oil.

MB 15 has also provided good service in racing shock absorbers (such as Ohlins) where this type of fluid is suitable.

MB 15 may also be used as a light industrial hydraulic oil in air line lubricators and other applications that require very light oils.

Penrite LHM Plus should be used for Citroen, BMW and Jaguar levelling systems where LHM or LHM Plus type fluids are specified.

MB 15 may also be used a light hydraulic oil in air tools and other applications requiring a light oil grade.

It is also ideal for use a motorcycle fork oil where "5W" Fork oils are specified.

CUSTOMER BENEFITS

- Provides wear protection
- Good low temperature flow properties

INDUSTRY SPECIFICATIONS

Penrite MB 15 Suspension Fluid meets the performance requirements of:

MB 343.0

ISO 15

Other available suspension fluids: Penrite LHM Plus, Penrite SSF and Penrite PAS Fluid.

Typical Properties

Density at 15°C, kg/L	0.835
Viscosity, Kinematic, cSt	
at 40°C	15.3
at 100°C	4.0
Viscosity Index	170
Zinc, mass %	Nil

Environment, Health and Safety