



CEPSA INITIAL PRODUCT RANGE

The below product range is our initial stock holding from CEPSA. More products can be made available. Data sheets are available on the shared drive under "Current Penrite Product Information" and these can be viewed for the full product information and applications.

Please note that volumes are limited for some grades.

CEPSA EUROTRANS SHPD SAE 10W-40

CEPEUROSHPD1040205

Full synthetic, OEM Approved, full SAPS engine oil for modern four stroke turbo charged and naturally aspirated engines. Compatible with SCR equipped trucks and buses. Suitable for use in cooled EGR or normal EGR.

Key Specifications: API CI-4/ACEA E4/E7, MB-Approval 228.5, Scania LDF-2 Approved

CEPSA EUROTRANS SHPD SAE 5W-30

CEPEUROSHPD530205

Full synthetic, OEM Approved, full SAPS engine oil for modern four stroke turbo charged and naturally aspirated engines. Compatible with SCR equipped trucks and buses. Suitable for use in cooled EGR or normal EGR. Can provide up to 4% fuel savings in heavy goods compared to 15W-40 oils.

Key Specifications: ACEA E4/E7, MB-Approval 228.5, Iveco 18-180 4FE, Renault RXD

CEPSA TRANSMISIONES FE+LD 75W-80

CEPFELD7580205, CEPFELD7580050

Full synthetic, OEM Approved fluid for manual gearboxes (including automated manual gearboxes) to provide long service life and smooth gear shifts. Ideal for AS Tronic gearboxes in trucks.

Key Specifications: ZF TE ML 02D Approved, API GL-4, Volvo 97305, MAN 341 Z-3/E-3

CEPSA TRANSMISIONES MBT 75W-90

CEPMBT7590205

Full synthetic, OEM Approved gear oil suitable for a wide range of vehicles. It is particularly recommended for Mercedes Benz ACTROS vehicles using the latest generation of synchronised boxes.

Key Specifications: MB- Approval 235.11, API GL-4

CEPSA TRANSMISIONES EP FE+LD 75W-90

CEPEPFELD7590205, CEPEPFELD7590050

Full synthetic, OEM Approved fluid for differentials and gearboxes that require long drains, durable shifts and special friction properties. Provides drain intervals of up to 120,000km to 160,000km.

Key Specifications: MB- Approval 235.8, API MT-1/GL-5, Scania STO 1:0, MAN 3343 Type S, ZF TE ML 02B/05B/07B/12B/16F/17B/19C/21B

CEPSA ATF 3000S

CEPEATF3000205

Full synthetic, OEM Approved, automatic transmission fluid for long service life in automotive and heavy duty transmissions.

Key Specifications: MB-Approval 236.9, ZF TE ML 09/14B/16L Approved, DEXRON®-IIIH, Allison C4

CEPSA BIO OIL HM-S ISO 46 AND 68

CEPBIO46200, CEPBIO68200

Ester based, synthetic biodegradable hydraulic oil compatible with commonly available gaskets and rubbers used in hydraulic systems (such as Viton, Perbunan, nitrile NBR, Neoprene, Silicone etc)

Key Specifications: VDMA 24568 Class HEES, ISO 15380 Class HEES, EU Ecolabel FR/27/07

CEPSA ECOBLUE

CEPECOBLUE010

EcoBlue is an Aqueous Solution of Urea 32.5% in weight, and its trade name is that of an automotive grade urea solution, AUS 32, AdBlue®. AdBlue® is a NOx reducing agent required by SCR technology in vehicles that must comply with the emissions rules imposed by the European regulations EURO 4 and EURO 5. May be used in both light duty and heavy duty vehicles.

Key Specifications: DIN 70070

