



TECHNICAL BULLETIN

No 86 May 2005

HPR 30 NOW API SM

We are pleased to announce that HPR 30 has been upgraded to the new API SM specification.

Using a combination of additives that is exclusively used by Penrite in Australia, this technology is the result of the latest advances in European research and developments.

Blending actually commenced in March and labeled product should be appearing in June.

PENRITE PREMIUM ENGINE OILS PERFORMANCE SUMMARY AT MAY 2005

Product	API	ACEA
<i>HPR 5</i>	<i>SM/CF</i>	<i>A3/B4</i>
<i>HPR 10</i>	<i>SM/CF</i>	<i>A3/B4</i>
<i>HPR15</i>	<i>SM/CF</i>	<i>A3/B4</i>
<i>HPR 30</i>	<i>SM/CF</i>	<i>A3/B3</i>
<i>HPR 40</i>	<i>SL/CF</i>	<i>A2</i>
<i>HPR 50</i>	<i>SL</i>	
<i>HPR Gas 10</i>	<i>CG-4/SL</i>	<i>A3/B4</i>
<i>HPR Gas</i>	<i>CG-4/SL</i>	<i>A3/B4</i>
<i>HPR Diesel 5</i>	<i>CH-4/SL</i>	<i>A3/B4</i>
<i>HPR Diesel 15</i>	<i>CH-4/SL</i>	<i>A3/B4</i>
<i>HPR Diesel</i>	<i>CH-4/SJ</i>	<i>A3/B4</i>
<i>Synthetic 5</i>	<i>SM/CF</i>	<i>A3/B4</i>
<i>Competition Engine Oil 15</i>	<i>SL/CF</i>	<i>A3/B4</i>
<i>Competition Engine Oil 25</i>	<i>SL/CF</i>	<i>A3/B4</i>