Page 1 of 12 Product: Brake and Parts Cleaner 20L

Issue Date: 13th March 2018 Revision: 1.0

SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

1.1 PRODUCT IDENTIFIER: Brake and Parts Cleaner 20L

1.2 PRODUCT CODE: MABAPC020

1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:

RELEVANT IDENTIFIED USES: Brake and parts cleaner.

RESTRICTIONS ON USE: None known.

1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

SUPPLIER NAME: PENRITE OIL Company Pty Ltd (ABN: 25005 001 525),
ADDRESS (Australia): 110-116 Greens Road, Dandenong South VIC, Australia, 3175
TELEPHONE NUMBER (Australia): 1300 736 748; +61 3 8710 6600 (Int); Fax: 1800 736 748

ADDRESS (New Zealand): 75 Lady Ruby Drive, East Tamaki, Auckland, New Zealand, 2013

TELEPHONE NUMBER (New Zealand):0800 533 698; Fax: 0800 533 698 E-MAIL: tech@penriteoil.com (Aust and NZ)

1.5 EMERGENCY TEL. NUMBER: Australia: 1300 736 748; New Zealand: 0800 533 698

(Poisons Information Centre (Aust 131 126; NZ 0800 764 766)

1.6 HSNO DETAILS:

HSNO APPROVAL NUMBER: HSR002528.

HSNO GROUP TITLE: Cleaning Products (Flammable) Group Standard 2017.

SECTION 2 – HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

GHS CLASSIFICATION HAZARD

CLASS & CATEGORY: Under the Model Work Health and Safety Regulations the product would be

rated as hazardous:

Flammable Liquids - Category 2
Aspiration Hazard - Category 1
Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Irritation - Category 2A

Specific Target Organ Toxicity (Single Exposure) - Category 3

Chronic Aquatic Toxicity - Category 2.

2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: Danger

PICTOGRAMS:



HAZARD STATEMENTS: H225 - Highly flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

PREVENTION: P102 - Keep out of reach of children.

P103 - Read label before use.

P210 - Keep away from heat, sparks, open flames and hot surfaces - No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, lighting equipment.

P242 - Use only non-sparking tools.

SECTION 2 – HAZARD(S) IDENTIFICATION Continued

PREVENTION (Continued): P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing mist, vapours and spray. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection/face protection.

RESPONSE: P101 - If medical advice is needed, have product container or label at hand.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTRE (phone

Australia 131 126; New Zealand 0800 764 766) or doctor/physician. P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTRE (phone Australia 131 126; New Zealand 0800

764 766) or doctor/physician if you feel unwell.

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

P370+P378 - In case of fire: Use carbon dioxide, alcohol resistant foam, dry

chemical or water spray for extinction.

P391 - Collect spillage.

STORAGE: P233 - Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

DISPOSAL: P501 - Dispose of contents/container in accordance with local regulations.

2.3 OTHER HAZARDS: This is a Schedule 5 Poison. Due to the presence of solvents there is a

possibility of organ system damage. The product is a highly flammable liquid and will potentially form flammable/explosive mixtures in air. There may be static discharge issues with the product that could lead to a fire. As for all chemical products, persons should not expose open wounds, cuts, abrasions

or irritated skin to this material.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Pentane, 2-methyl- [Isohexane]	107-83-5	> 60%	Flam Liq 2 - H225 Asp Haz 1 - H304 Skin Irrit 2 - H315 STOT SE 3 - H336 Chron Aq Tox 2 - H411
2-Propanol	67-63-0	10% - 20%	Flam Liq 2 - H225 Eye Irrit 2A - H319 STOT SE 3 - H336
2-Propanone [Acetone]	67-64-1	< 10%	Flam Liq 2 - H225 Eye Irrit 2A - H319 STOT SE 3 - H336 AUH066

^{*} Please see Section 15 of this SDS for the full text description of the Label Elements.

SECTION 4 – FIRST AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION:

Rinse mouth out with water. If swallowed, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Within 6 hours of ingestion, if delayed symptoms, such as a fever greater than 38.3°C, shortness of breath, chest congestion or continued coughing/wheezing occurs transport immediately to a medical facility. As the product is hydrocarbon based and of low viscosity (<20.5cSt @ 40°C), if ingested seek urgent medical assistance.

EYE:

If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a Doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. As the product is rated as an eye irritant, after flushing, it is recommended that you seek medical assistance taking this Safety Data Sheet or the container with you.

SKIN CONTACT:

If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. As the product is rated as a skin irritant, after washing if skin irritation occurs, it is recommended that you seek medical advice/attention taking this Safety Data Sheet with you.

INHALATION:

If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment, once environment has been assessed for flammable vapours. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If the person feels unwell and symptoms, such as dizziness or uncoordination occur, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops or persists, consult a Doctor.

PROTECTION FOR FIRST AIDERS:

No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for flammable vapours before entering. Never enter an environment with a flammable atmosphere. Do not enter contaminated area without a respirator or Self Contained Breathing Apparatus once you have assessed the atmosphere. As the product is hydrocarbon based and of low viscosity, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

FIRST AID FACILITIES:

Eye wash fountain and safety showers are recommended in the area where the product is used.

4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:The product is rated as a skin and eve irritant by calculation. Skin contact m

The product is rated as a skin and eye irritant by calculation. Skin contact may lead to redness or itching. Eye contact may lead to localised burning, redness, pain, swelling and tearing. Vapours may cause drowsiness or dizziness. Inhalation of high vapour concentrations may cause central nervous system depression resulting in dizziness, headache, nausea and possible loss of coordination. Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. The product is an aspiration hazard. If material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever.

SECTION 4 – FIRST AID MEASURES Continued

CHRONIC: Repeated or prolonged skin contact may cause removal of natural fat from the

skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated or prolonged skin contact may also aggravate/exacerbate existing

skin conditions, such as dermatitis.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY:

ADVICE TO DOCTOR:

Treat symptomatically. As the product is hydrocarbon based and of low viscosity, if vomiting has occurred after ingestion, the patient should be monitored for adverse effects to ensure that the product has not aspirated into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Inhalation of high vapour concentrations may cause central nervous system depression.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE MEDIA: Use extinguishing media appropriate for surrounding fire. Use carbon dioxide,

alcohol resistant foam, dry chemicals or water spray. Spray down fumes

resulting from fire.

UNSUITABLE MEDIA: Avoid using full water jet directed at residual material that may be burning.

Water may cause splattering on hot residues.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

COMBUSTION HAZARDS: Combustion may produce oxides of carbon, as well as smoke and irritating

vapours.

5.3 ADVICE FOR FIREFIGHTERS:

FIRE: This product is highly flammable with a typical flash point of <-9°C. The vapour

is heavier than air and will spread along the ground and may accumulate in low points or depressions. Therefore, ignition may occur well away from the point of release of the material. Keep storage tanks, pipelines, fire exposed surfaces,

etc. cool with water spray.

HAZCHEM CODE: ·3YE.

EXPLOSION: No information to indicate that the product is an explosion hazard; though the

solvent component will form an explosive mixture with air. NOTE: Under the WHS legislation, this product is rated as Flammable Liquid - Category 2, with a typical Flash point of <-9°C. Extinguish all sources of flame or spark. Closed

containers may explode when exposed to extreme heat.

PROTECTIVE

EQUIPMENT: In the event of a fire, wear full protective clothing and self-contained breathing

equipment with full-face piece operated in the pressure demand or other

positive pressure mode.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PROTECTION:

For small spills, wear Nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill in the open a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency and whether the atmosphere is flammable. If in doubt about potential oxygen deficiency, wear self-contained breathing apparatus. Never enter an environment with a flammable atmosphere.

SECTION 6 – ACCIDENTAL RELEASE MEASURES Continued

CONTROL MEASURES:

Ventilate area and extinguish and/or remove all sources of ignition. CAUTION: Vapour may form an explosive mixture with air. Never enter a spill area unless you know the vapours have dissipated to make the area safe. Stop the leak if safe to do so. CAUTION: The spilled product will be slippery. Avoid contact with the spilled material.

EMERGENCY PROCEDURES: In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE:

Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs. Take precautions against static discharge. Ensure all equipment is grounded and use non-sparking tools during clean up operations.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAINMENT:

Personnel must wear the appropriate clothing as required in Section 6.1 during containment procedures; after the environment has been evaluated. Contain the spill and absorb with a proprietary absorbent material, sand or earth. CAUTION: The spilled product will be slippery. Be careful of static discharges and/or sparking during clean up. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

CLEANING PROCEDURES:

Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Be careful of static discharges and/or sparking during clean up. Use only non-sparking tools during cleaning operations. CAUTION: The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped, using flammable liquid equipment, into vessels and returned for reprocessing or destruction. Personnel must wear the appropriate clothing as required in Section 6.1 during cleaning procedures; after the environment has been evaluated. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

SECTION 7 - HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Extinguish any potential sources of ignition before using as flammable vapours will be generated during application. Do not leave containers in direct sunlight. Due to the possibility of pressure build up in the container, open the container with care. Avoid breathing mists or vapours. Do not smoke when handling the material. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Please note that flammable mixtures may be formed when residual material remains in empty containers. Prevent product from entering waterways, drains or sewers. There is the potential for electrostatic accumulation in the product. As a precaution, containers should always be earthed before dispensing commences.

SECTION 7 - HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED Continued

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

SAFE STORAGE:

This product is classified as a Class 3 Flammable Liquid (Typical Flash Point <-9°C). Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. It is recommended that the product is stored below 25°C.

INCOMPATIBILITIES: Oxidising substances including strong acids.

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 EXPOSURE CONTROL MEASURES:

EXPOSURE LIMIT VALUES: Exposure

Exposure standards for the product have not been established. The following values are applicable for the major component:

values are applicable for the major component

Isohexane (2-Methyl pentane) ACGIH

TWA: 500 ppm 1760 mg/m³ STEL: 1000 ppm 3500 mg/m³

Acetone (2-Propanone)

TWA: 500 ppm 1185 mg/m³ STEL: 1000 ppm 2375 mg/m³

2-Propanol

TWA: 400 ppm 983 mg/m³ STEL: 500 ppm 1230 mg/m³

8.2 BIOLOGICAL

MONITORING: No data available.

8.3 CONTROL BANDING: No data available.

8.4 ENGINEERING CONTROLS:

ENGINEERING CONTROLS:

Special ventilation is not normally required when using this product in normal use scenarios. However, in the operation of certain equipment, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. PLEASE NOTE: Due to the highly flammable nature of the product, if there is a necessity to use ventilation equipment it should not be a potential source of ignition for any vapours generated.

8.5 INDIVIDUAL PROTECTION MEASURES:

EYE & FACE PROTECTION: Wear safety glasses/goggles to avoid eye contact when handling. If there is a

risk of splashing during use, a full face shield is recommended. Use eye

protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of contact with the material wear gloves to provide hand

protection. Nitrile rubber gloves are recommended.

SKIN (CLOTHING)

PROTECTION: During normal operating procedures, long sleeved clothing is recommended to

avoid skin contact. Soiled clothing should be washed with detergent prior to re-

use.

RESPIRATORY PROTECTION: During routine operation a respirator is not required. However, if mists or

vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS

1716.

THERMAL PROTECTION: Not applicable.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Clear liquid.

ODOUR: Characteristic hydrocarbon solvent odour.

ODOUR THRESHOLD: No data available. Not applicable. :Ha MELTING/FREEZING POINT: No data available. No data available. **INITIAL BOILING POINT: BOILING RANGE (°C):** No data available. FLASHPOINT (°C): Typically <-9°C **EVAPORATION RATE:** No data available. FLAMMABILITY LIMITS (%): No data available. VAPOUR PRESSURE (kPa): No data available. **VAPOUR DENSITY:** No data available.

SOLUBILITY IN WATER(g/L): Partially miscible with water due to the presence of acetone.

Typically 0.69.

PARTITION COEFFICIENT: No data available for the product.

AUTO-IGNITION TEMP (°C): No data available.

DECOMPOSITION TEMP (°C): No data available.

VISCOSITY (cst @ 100°C): No data available.

VISCOSITY (cst @ 40°C): Typically <20.5cSt.

SECTION 10 – STABILITY AND REACTIVITY

10.1 REACTIVITY: The product does not pose any further reactivity hazards other than those listed

in the following sub-sections. With its low flash point the product may form

explosive mixtures with air at room temperature.

10.2 CHEMICAL STABILITY: Stable under recommended storage and handling conditions (see section 7).

10.3 POSSIBILITY OF

DENSITY @ 15.0°C:

HAZARDOUS REACTIONS: Keep away from strong oxidising agents, such as strong acids, chlorates,

nitrates and peroxides. Hazardous polymerisation does not occur.

10.4 CONDITIONS TO AVOID: The product has a flash point of Typically <-9°C. Avoid ignition sources

including heat and sparks. Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open

when not in use.

10.5 INCOMPATIBLE

MATERIALS: Strong oxidising agents including concentrated acids.

10.6 HAZARDOUS DECOMPOSITION

PRODUCTS: Hazardous decomposition products are not expected to form during normal

storage requirements. See Section 5.2 for Hazardous Combustion products.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and test data is not available for the product as a whole.

11.2 SWALLOWED: This is a Schedule 5 Poison. As the product is hydrocarbon based and the

viscosity is low, caution should be taken in respect to aspiration into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Ingestion of large amounts may lead to nausea and vomiting. During normal usage

ingestion should not be a means of exposure.

SECTION 11 – TOXICOLOGICAL INFORMATION Continued

11.3 SKIN CORROSION/ IRRITATION:

This product is rated as Causes skin irritation. Symptoms may include redness or itching. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.

11.4 SERIOUS EYE DAMAGE/

IRRITATION:

This product is rated as Causes serious eye irritation. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.

11.5 RESPIRATORY OR

SKIN SENSITISATION: This product is not expected to be a skin sensitiser based on the available data

and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.

11.6 GERM CELL **MUTAGENICITY:**

This product is not expected to be mutagenic based on the available data and the known hazards of the components.

11.7 CARCINOGENICITY:

This product is not expected to be a carcinogen based on the available data and the known hazards of the components.

11.8 REPRODUCTIVE

TOXICITY:

This product is not expected to be a reproductive hazard based on the available data and the known hazards of the components.

11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

SINGLE EXPOSURE:

This product is rated as May cause drowsiness and dizziness. It contains volatile hydrocarbon components, hence inhalation of vapours or mist may cause irritation to the nose and throat. Inhalation of high vapour concentrations may cause central nervous system depression resulting in dizziness, headache, nausea and possible loss of coordination. Exposure to high levels of hydrocarbon solvent vapours may impact on the liver and kidneys.

11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

REPEATED EXPOSURE:

There is no data available for the product as a whole. This product is not expected to cause organ damage from prolonged or repeated exposure based on the available data and the known hazards of the components. However, as the product is hydrocarbon based care should be taken as repeated or prolonged exposure to hydrocarbons.

11.11 ASPIRATION HAZARD: This product is rated as an aspiration hazard - May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. This can be fatal. As the product is hydrocarbon based, if the product has been ingested or vomiting has occurred after ingestion, the patient must seek urgent medical attention and should be monitored for adverse effects.

11.12 OTHER INFORMATION: There is no additional information available.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 ECOTOXICITY: The manufacturer nominates the following Ecotoxicity data:

Isohexane

EC₅₀ (Crustacea, 48hr): 0.64 mg/L

Isopropanol

EC₅₀ (Crustacea, 48hr): 12,500 mg/L EC₅₀ (Algae, 72hr): >1,000 mg/L LC₅₀ (Fish, 96hr): >1,400 mg/L

Acetone

EC₅₀ (Crustacea, 48hr): >100 mg/L EC₅₀ (Algae, 96hr): 20.565 mg/L LC₅₀ (Fish, 96hr): >100 mg/L

There is no data available for the product as a whole. However, some of the components have been rated as Toxic to aquatic life with long lasting effects and Harmful to aquatic life with long lasting effects. Based upon these nominated values the product is expected to be Toxic to aquatic life with long lasting effects.

12.2 PERSISTENCE & DEGRADABILITY:

There is no data available for the product as a whole. The manufacturer has nominated that the Persistence of the ingredients in Water and soil is low.

12.3 BIOACCUMULATIVE POTENTIAL:

There is no data available for the product as a whole. The manufacturer has nominated that the Log Kow for the ingredients are Isohexane = 3.2145; and, Isopropanol = 0.05. The Acetone BCF is 0.69.

12.4 MOBILITY IN SOIL:

There is no data available for the product as a whole. The manufacturer has nominated that the mobility of Isohexane in soil is low with a KOC = 124.9; and, is high for Isopropanol (KOC = 1.06) and Acetone (KOC = 1.981).

12.5 OTHER ADVERSE

EFFECTS: There is no data available for the product as a whole.

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 DISPOSAL METHODS: PRODUCT:

The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. Note: Waste product must be handled as a Flammable liquid.

CONTAINERS:

Empty containers may contain residual product. CAUTION: Residues are highly flammable and will ignite with a source of ignition. Containers should be completely drained in a well ventilated area where vapours cannot accumulate and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. As containers may contain highly flammable residues, they should not be pressurised, cut by a grinder, drilled or exposed to heat, flames or other sources of ignition. Closed containers when exposed to such conditions/treatment may explode causing serious injury.

SECTION 14 – TRANSPORT INFORMATION

This product is regulated for land, sea or air transportation. (HS Code: 2710.12.90) (Limited quantities of 1L apply)

14.1 LAND (ADG Code):

UN NUMBER: 1993

UN PROPER SHIPPING

NAME: FLAMMABLE LIQUID, N.O.S. (Contains Isohexane, Acetone and

Isopropanol).

TRANSPORT HAZARD

CLASS(ES): 3
PACKAGING GROUP: ||

ENVIRONMENTAL

HAZARDS: Yes

SPECIAL PRECAUTIONS

FOR USER: 274. HAZCHEM CODE: 3YE

14.2 SEA (IMDG):

UN NUMBER: 1993

UN PROPER SHIPPING

NAME: Flammable Liquid, n.o.s. (Contains Isohexane, Acetone and Isopropanol).

TRANSPORT HAZARD

CLASS(ES): 3
PACKAGING GROUP: ||

ENVIRONMENTAL

HAZARDS: Yes

SPECIAL PRECAUTIONS

FOR USER: A3

14.3 AIR (IATA):

UN NUMBER: 1993

UN PROPER SHIPPING

NAME: FLAMMABLE, LIQUID, N.O.S (Contains Isohexane, Acetone and

Isopropanol).

TRANSPORT HAZARD

CLASS(ES): 3
PACKAGING GROUP: ||

ENVIRONMENTAL

HAZARDS: Yes (Marine Pollutant)

SPECIAL PRECAUTIONS

FOR USER: 274.

SECTION 15 – REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:

APPLICABLE REGULATIONS:

SUSMP: Schedule 5.

AICS: All ingredients are on the AICS List.

MONTREAL PROTOCOL: No data available. STOCKHOLM CONVENTION: No data available. ROTTERDAM CONVENTION: No data available. No data available. No data available.

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM

SHIPS (MARPOL): Not applicable.

SECTION 15 – REGULATORY INFORMATION Continued

OTHER REGULATORY INFORMATION:

GHS CLASSIFICATION HAZARD CLASS & CATEGORY

AND HAZARD STATEMENT: Flammable Liquids Category 2; H225 - Highly flammable liquid and vapour.

Aspiration Hazard Category 1; H304 - May be fatal if swallowed and enters

airways.

Skin Corrosion/Irritation Category 2; H315 - Causes skin irritation.

Serious Eve Damage/Irritation Category 2A: H319 - Causes serious eve

irritation.

Specific Target Organ Toxicity (Single Exposure) Category 3: H336 - May

cause drowsiness or dizziness.

Chronic Aquatic Toxicity Category 2; H411 - Toxic to aquatic life with long

lasting effects.

AUH066 - Repeated exposure may cause skin dryness or cracking.

HSNO APPROVAL NUMBER: HSR002528.

HSNO GROUP TITLE: Cleaning Products (Flammable) Group Standard 2017.

SECTION 16 – ANY OTHER RELEVANT INFORMATION

SDS INFORMATION:

Date of SDS Preparation: 13th March 2018 Revision: 1.0 Changes to product formulation. Changes in Sections 2, 3, 4, 5, 6, 8, 9, 11, 12

13, 14, 15 and 16.

ACRONYMS:

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

CAS Number Chemical Abstracts Service Registry Number

EINECS European Inventory of Existing Commercial Chemical Substances

UN Number United Nations Number

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists
HSE-WEL Health and Safety Executive - Workplace Exposure Limit

EH40 EH40/2005 Workplace Exposure Limits
IMDG International Maritime Dangerous Goods
IATA International Air Transport Association

IUCLID International Uniform Chemical Information Database RTECS Registry of Toxic Effects of Chemical Substances

%W/W Percent weight for weight

OECD Organisation for Economic Co-Operation and Development

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

HAZCHEM Code Emergency action code of numbers and letters which gives information to emergency services

NOHSC National Occupational Health and Safety Commission

NICNAS National Industrial Chemicals Notification & Assessment Scheme

IMAP Inventory Multi-Tiered Assessment and Prioritisation AICS Australian Inventory of Chemical Substances

TWA Time-Weighted Average STEL Short Term Exposure Limit

HSNO Hazardous Substances and New Organisms Act 1996

GHS Globally Harmonised System of Classification and Labelling of Chemicals

WHS Work Health and Safety
PPE Personal Protective Equipment.

LD₅₀ Median Lethal Dose

LC₅₀ Median Lethal Concentration

EC₅₀ Effective Concentration of a substance that causes 50% of the maximum response after

exposure for a nominated time

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
ECHA European Chemicals Agency

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

HCIS Hazardous Chemical Information System

SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued

LITERATURE REFERENCES AND SOURCES OF DATA:

OECD Guidelines for Testing of Chemicals

Annex I: OECD Test Guidelines for Studies Included in SIDS

Manual for the Assessment of Chemicals Chapter 2 Data Gathering

International Toxicity Testing Guidelines

Hazardous Substance Information System - Guidance Material for Hazard Classifications

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Model Work Health and Safety Regulations.

Model Work Health and Safety Regulations - Transitional Principles

Workplace Exposure Standards for Airborne Contaminants

Australian Dangerous Goods Code 7th Edition

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]

Guidance on the Classification of Hazardous Chemicals under the WHS Regulations

Assigning a Hazardous Substance to a Group Standard

User Guide to the HSNO Thresholds and Classifications

Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances

Correlation between GHS and New Zealand HSNO Hazard Classes and Categories

HSNO Control Regulations

Record of Group Standard Assignment

Labelling of Hazardous Substances Hazard and Precautionary Information

Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996

Workplace Exposure Standards and Biological Exposure Indices

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.