Page 1 of 10 Product: Silicone Brake Fluid Issue Date: 26<sup>th</sup> July 2016 Revision: 0.1

## SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL IDENTITY

1.1 PRODUCT IDENTIFIER: Silicone Brake Fluid

1.2 PRODUCT CODE: BFSIL

1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:

**RELEVANT IDENTIFIED USES:** Silicone fluid for braking systems.

**RESTRICTIONS ON USE:** None known.

1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

SUPPLIER NAME: PENRITE OIL Company Pty Ltd (ABN: 25005 001 525),
ADDRESS (Australia): 110-116 Greens Road, Dandenong South VIC, Australia, 3175
TELEPHONE NUMBER (Australia): 1300 736 748; +61 3 9801 0877 (Int); Fax: 1800 736 748

ADDRESS (New Zealand): 75 Lady Ruby Drive, East Tamaki, Auckland, New Zealand, 2013

**TELEPHONE NUMBER (New Zealand):**0800 533 698; Fax: 0800 533 698 **E-MAIL:** tech@penriteoil.com (Aust and NZ)

**1.5 EMERGENCY TEL. NUMBER:** Australia: 1300 736 748; New Zealand: 0800 533 698

(Poisons Information Centre (Aust 131 126; NZ 0800 764 766)

1.6 HSNO DETAILS:

HSNO APPROVAL NUMBER: HSR002606.

HSNO GROUP TITLE: Lubricants, Lubricant Additives, Coolants and Anti-Freeze Agents

(Subsidiary Hazard) Group Standard, 2006.

## SECTION 2 – HAZARD(S) IDENTIFICATION

#### 2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

**GHS CLASSIFICATION HAZARD** 

CLASS & CATEGORY: Under the Model Work Health and Safety Regulations, the product would not

be classified as hazardous.

#### 2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: Not Applicable. PICTOGRAMS: Not Applicable. HAZARD STATEMENTS: Not Applicable.

#### PRECAUTIONARY STATEMENTS:

PREVENTION: Not Applicable.
RESPONSE: Not Applicable.
STORAGE: Not Applicable.
DISPOSAL: Not Applicable.

2.3 OTHER HAZARDS: The mixture has a low order of toxicity associated with it. Excessive exposure

may result in mild irritation to the skin, eye or respiratory system. Prolonged or repeated contact may cause defatting of the skin which may lead to dermatitis. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated

skin to this material.

Page 2 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

## **SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS**

INGREDIENTSCAS NUMBERConcentration<br/>% W/WGHSPhosphoric acid, tributyl ester126-73-8< 1.0%</td>Acut Tox 4 - H302<br/>Skin Irrit 2 - H315<br/>Acut Tox 3 - H331

Carc Cat 2 - H351 Chron Aq Tox 3 - H412

Polydimethylsiloxane blend with added inhibitors - To 100% Not Applic Not Applic = Not Applicable \*Please see Section 15 of this SDS for full text description of the Label Elements.

### SECTION 4 - FIRST AID MEASURES

#### 4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION:

Rinse mouth out with water. Due to the blend of ingredients present, the manufacturer recommends that if swallowed, do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. If irritation develops or persists or vomiting has occurred after ingestion, seek medical assistance.

EYE:

If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation develops or persists, seek medical assistance.

**SKIN CONTACT:** 

If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. If irritation develops or persists, consult a Doctor.

**INHALATION:** 

If affected, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If irritation develops/persists, consult a Doctor.

PROTECTION FOR FIRST AIDERS:

No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for vapours before entering. Do not enter contaminated area without a respirator. As the product is silicone based, if the person has ingested the product, do not use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

**FIRST AID FACILITIES:** 

Eye wash fountain and safety showers are recommended in the area where the product is used.

#### 4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:

**ACUTE:** 

Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. Eye contact may lead to localised burning, redness and tearing. Skin contact may lead to redness or itching.

CHRONIC:

Skin contact may aggravate/exacerbate existing skin conditions, such as dermatitis.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY: ADVICE TO DOCTOR: Treat symptomatically.

Page 3 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

### SECTION 5 – FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

**SUITABLE MEDIA:** Use extinguishing media appropriate for surrounding fire. Use carbon dioxide,

foam, dry chemical or water spray. Spray down fumes resulting from fire.

**UNSUITABLE MEDIA:** Avoid using full water jet directed at residual material that may be burning.

Water may cause splattering on hot residue.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

**COMBUSTION HAZARDS:** Combustion may produce silica, oxides of carbon, as well as smoke and

irritating vapours.

5.3 ADVICE FOR FIREFIGHTERS:

FIRE: The product is not flammable under conditions of use. This is a silicone based

liquid that will burn if preheated - Typical Flash Point >150°C. Keep storage

tanks, pipelines, fire exposed surfaces, etc. cool with water spray.

**HAZCHEM CODE:** Not applicable.

**EXPLOSION:** No information to indicate that the product is an explosion hazard. Extinguish all

sources of flame or spark. Closed containers may explode when exposed to

extreme heat.

**PROTECTIVE** 

In the event of a fire, wear full protective clothing and self-contained breathing **EQUIPMENT:** 

equipment with full-face piece operated in the pressure demand or other

positive pressure mode.

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

#### 6.1 PERSONAL PRECAUTIONS. PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PROTECTION:

For small spills, wear Natural rubber, Butyl rubber, Nitrile or PVC gloves, glasses/goggles, boots and full-length clothing. During routine operation a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency. If in doubt about potential

oxygen deficiency wear self-contained breathing apparatus.

CONTROL MEASURES: Ventilate area and extinguish and/or remove all sources of ignition. Stop the

leak if safe to do so. CAUTION: The spilled product will be slippery. Avoid

contact with the spilled material.

EMERGENCY PROCEDURES: In the event of a spill or accidental release, notify the relevant authorities in

accordance with all applicable regulations.

**6.2 ENVIRONMENTAL PRECAUTIONS:** 

SPILL ADVICE: Do not allow product to enter drains, surface water, sewers or watercourses -

inform local authorities if this occurs.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

**CONTAINMENT:** Contain the spill and absorb with a proprietary absorbent material, sand or

> earth. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains

are covered, to minimise the potential for this to occur.

Page 4 of 10 Product: Silicone Brake Fluid

# SAFETY DATA SHEET

### SECTION 6 – ACCIDENTAL RELEASE MEASURES Continued

#### **CLEANING PROCEDURES:**

Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped into vessels and returned for reprocessing or destruction. Personnel must wear gloves, goggles or glasses, boots and full-length clothing during cleaning procedures. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

#### HANDLING AND STORAGE, INCLUDING HOW SECTION 7 THE CHEMICAL MAY BE SAFELY USED

#### 7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers.

#### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

SAFE STORAGE:

Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs, animal feed and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. Keep out of reach of children.

**INCOMPATIBILITIES:** 

Mineral oils and strong oxidizing substances including strong acids and bases.

#### SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

#### **8.1 EXPOSURE CONTROL MEASURES:**

**EXPOSURE LIMIT VALUES:** Exposure standards for the product have not been established. However, in the operation of certain equipment or at elevated temperatures, if vapours or mists are generated, the following Exposure Standard must be observed:

> Phosphoric acid, tributyl ester: TWA: 0.2 ppm 2.2 ma/m3

**8.2 BIOLOGICAL** 

**MONITORING:** No data available.

**8.3 CONTROL BANDING:** No data available.

#### **8.4 ENGINEERING CONTROLS:**

**ENGINEERING CONTROLS:** 

Special ventilation is not normally required when using this product in normal use scenarios. However, in the operation of certain equipment, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation.

Page 5 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

### SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION Cont'd

**8.5 INDIVIDUAL PROTECTION MEASURES:** 

EYE & FACE PROTECTION: Wear safety glasses/goggles to avoid eye contact when handling. If there is a

risk of splashing during use, a full face shield is recommended. Use eye

protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of contact with the material wear gloves to provide hand

protection. Natural rubber, Butyl rubber, Nitrile or PVC gloves are

recommended.

SKIN (CLOTHING)

**PROTECTION:** During normal operating procedures, long sleeved clothing is recommended to

avoid skin contact. Soiled clothing should be washed with detergent prior to re-

use.

**RESPIRATORY PROTECTION:** During routine operation a respirator is not required. However, if mists or

vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS

1716.

THERMAL PROTECTION: Not applicable.

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 PHYSICAL AND CHEMICAL PROPERTIES: APPEARANCE:** Purple liquid.

ODOUR: Minor odour.
ODOUR THRESHOLD: No data available.
Purple liquid.
Minor odour.
No data available.
Not applicable.

MELTING/FREEZING POINT: < -50°C.
INITIAL BOILING POINT: > 260°C.

**BOILING RANGE (°C):** No data available.

FLASHPOINT (°C): > 150°C

EVAPORATION RATE: Negligible.

FLAMMABILITY LIMITS (%): No data available.

VAPOUR PRESSURE @ 20°C: < 2 millibars.

VAPOUR DENSITY: No data available

DENSITY (kg/L @ 20°C): Typically 0.955.

**SOLUBILITY IN WATER(g/L):** Immiscible with water, partly soluble in ethanol.

**PARTITION COEFFICIENT:** No data available.

AUTO-IGNITION TEMP (°C): > 400°C.

DECOMPOSITION TEMP (°C): > 400°C.

VISCOSITY (cSt @ 100°C): Typically 13.9.

VISCOSITY (cSt @ 20°C): Typically 35 - 50.

VISCOSITY (cSt @ -40°C): Typically 150.

### SECTION 10 - STABILITY AND REACTIVITY

**10.1 REACTIVITY:** The product does not pose any further reactivity hazards other than those listed

in the following sub-sections.

10.2 CHEMICAL STABILITY: Stable under recommended storage and handling conditions (see section 7).

The product will decompose at temperatures > 400°C.

10.3 POSSIBILITY OF

**HAZARDOUS REACTIONS:** Keep away from mineral oils and strong oxidising agents and bases. Hazardous

polymerisation does not occur.

10.4 CONDITIONS TO AVOID: Observe the usual precautionary measures for handling chemicals. Do not heat

the container, leave it in direct sunlight or leave the container open when not in

use. Avoid sources of ignition.

Page 5 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

### **SECTION 10 – STABILITY AND REACTIVITY Continued**

**10.5 INCOMPATIBLE** 

MATERIALS: Strong oxidising agents including strong acids and bases, and mineral oils. As

a general precaution never mix brake fluids with other materials.

10.6 HAZARDOUS DECOMPOSITION

PRODUCTS: Hazardous decomposition products are not expected to form during normal

storage requirements. See Section 5.2 for Hazardous Combustion products.

### **SECTION 11 – TOXICOLOGICAL INFORMATION**

#### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and the manufacturer has nominated the following for the product:

Oral -  $LD_{50}$  (Rat): >5000 mg/kg Dermal -  $LD_{50}$  (Rabbit): >3000 mg/kg

Phosphoric acid, tributyl ester (IMAP)

Oral - LD<sub>50</sub> (Rat): >1390 mg/kg bw Oral - LD<sub>50</sub> (Mouse): >400 mg/kg bw Oral - LD<sub>50</sub> (Hen): >1500 mg/kg bw Dermal - LD<sub>50</sub> (Rabbit): >3100 mg/kg bw Dermal - LD<sub>50</sub> (Guinea pig): >9700 mg/kg bw

Inhalation - LC<sub>50</sub> (Male rat, air, 4 hours): >4242 mg/m<sup>3</sup>

11.2 SWALLOWED:

This product is expected to have a low order of toxicity associated with it when ingested. It may cause slight irritation to the mouth, throat and digestive tract. This product contains a component that is rated as Harmful if swallowed, however this is present at amounts well below the Concentration cut-off levels. During normal usage ingestion should not be a means of exposure.

11.3 SKIN CORROSION/ IRRITATION:

This product is not expected to exhibit Dermal Corrosivity/Irritation according to OECD Test 404, based on the available data and the known hazards of the components. May be mildly irritating to the skin. This product contains a component that is rated as Causes skin irritation, however this is present at amounts well below the Concentration cut-off levels. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to exacerbate the condition.

11.4 SERIOUS EYE DAMAGE/ IRRITATION:

This product is not expected to exhibit Eye Irritation or Serious Damage/Corrosivity according to OECD Test 405, based on the available data and the known hazards of the components. May be mildly irritating to the eyes. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye irritation.

11.5 RESPIRATORY OR SKIN SENSITISATION:

This product is not expected to be a skin sensitiser according to OECD Test 406, based on the available data and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards of the components.

11.6 GERM CELL MUTAGENICITY:

This product is not expected to be mutagenic according to tests such as OECD Tests 471, 475, 476, 478 and 479, based on the available data and the known hazards of the components.

11.7 CARCINOGENICITY:

This product is not expected to be a carcinogen according to OECD Test 451, based on the available data and the known hazards of the components. The product contains < 1% of Phosphoric acid, tributyl ester, which is rated as Carcinogenic Category 2: H351 - Suspected of causing cancer. However, this is present at amounts well below the Concentration cut-off levels.

Page 7 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

## **SECTION 11 – TOXICOLOGICAL INFORMATION Continued**

11.8 REPRODUCTIVE

TOXICITY:

This product is not expected to be a reproductive hazard based on the available

data and the known hazards of the components.

11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

SINGLE EXPOSURE:

This product is not expected to cause organ damage from a single exposure, based on the available data and the known hazards of the components. This product is not expected to pose an irritation hazard at ambient temperature or under normal handling conditions. Not classified as a respiratory irritant, however inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose, throat and respiratory system. This product contains a component that is rated as Toxic if inhaled, however this is present at amounts well below the Concentration cut-off levels where it is considered hazardous.

11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

REPEATED EXPOSURE: This product is not expected to cause organ damage from prolonged or

repeated exposure according to tests such as OECD Tests 410 and 412, based

on the available data and the known hazards of the components.

11.11 ASPIRATION HAZARD: This product is not expected to be an aspiration hazard, based on the available

data and the known hazards of the components.

11.12 OTHER INFORMATION: No additional information is available.

#### SECTION 12 – ECOLOGICAL INFORMATION

12.1 ECOTOXICITY: The product is of low acute ecotoxicity. The Phosphoric acid, tributyl ester

component has been rated as Harmful to aquatic life with long lasting effects. Based upon the calculated values the product is not expected to be rated.

12.2 PERSISTENCE &

**DEGRADABILITY:** 

Based on the available data and the known hazards of the components and similar products the product is expected to be inherently biodegradable. The manufacturer states that if the product is admitted into adapted biological water treatment plants in small quantities, no adverse effects on the degrading action

of the live sludge are expected.

12.3 BIOACCUMULATIVE

POTENTIAL:

Based on the available data and the known hazards of the components the

manufacturer states that the product is not expected to bioaccumulate.

**12.4 MOBILITY IN SOIL:** 

The product is insoluble in water and floats on the aqueous phase. Volatilisation from water to air is not expected. The product would have limited mobility in soil.

12.5 OTHER ADVERSE

**EFFECTS:** 

The product is considered to be neither "persistent, bio-accumulating and toxic" nor "very persistent and very bio-accumulating" according to Annex XIII of

Regulation EC 1907/2006.

### **SECTION 13 – DISPOSAL CONSIDERATIONS**

13.1 DISPOSAL METHODS: PRODUCT:

The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is also suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. Do not mix new or used brake fluid with solvents, lubricating oils or coolants when disposing. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations.

Page 8 of 10 Product: Silicone Brake Fluid

## **SAFETY DATA SHEET**

#### SECTION 13 – DISPOSAL CONSIDERATIONS Continued

**CONTAINERS:** 

Empty containers may contain residual product. They should be completely drained and then stored until reconditioned or disposed of. Empty drums should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. Where the containers are of metal construction they should not be pressurised, cut by a grinder, welded, brazed, soldered, drilled or exposed to heat, flames or other sources of ignition. Closed metal containers when exposed to such conditions/treatment may explode causing serious injury or death.

## **SECTION 14 – TRANSPORT INFORMATION**

This product is not regulated for land, sea or air transportation. (HS Code: 3819.00.00)

14.1 LAND (ADG Code):

**UN NUMBER:** Not applicable

**UN PROPER SHIPPING** 

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

**ENVIRONMENTAL** 

HAZARDS: Not applicable

**SPECIAL PRECAUTIONS** 

FOR USER: Not applicable HAZCHEM CODE: Not applicable

14.2 SEA (IMDG):

**UN NUMBER:** Not applicable

**UN PROPER SHIPPING** 

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

**ENVIRONMENTAL** 

HAZARDS: Not applicable

**SPECIAL PRECAUTIONS** 

FOR USER: Not applicable

14.3 AIR (IATA):

UN NUMBER: Not applicable

**UN PROPER SHIPPING** 

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

**ENVIRONMENTAL** 

HAZARDS: Not applicable

**SPECIAL PRECAUTIONS** 

FOR USER: Not applicable

Page 9 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

### **SECTION 15 – REGULATORY INFORMATION**

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:

**APPLICABLE REGULATIONS:** 

SUSMP: Not scheduled.

AICS:
MONTREAL PROTOCOL:
STOCKHOLM CONVENTION:
ROTTERDAM CONVENTION:
BASEL CONVENTION:
All ingredients are on the AICS List.
Not applicable to this product.
Not applicable to this product.
Not applicable to this product.

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM

SHIPS (MARPOL): Not determined.

OTHER REGULATORY INFORMATION:

**GHS CLASSIFICATION HAZARD CLASS & CATEGORY** 

AND HAZARD STATEMENT: Acute Toxicity - Oral Category 4; H302 - Harmful if swallowed.

Skin Corrosion/Irritation Category 2; H315 - Causes skin irritation. Acute Toxicity - Inhalation Category 3; H331 - Toxic if inhaled. Carcinogenicity Category 2; H351 - Suspected of causing cancer.

Chronic Aquatic Toxicity Category 3; H412 - Harmful to aquatic life with long

lasting effects.

HSNO APPROVAL NUMBER: HSR002606

HSNO GROUP TITLE: Lubricants, Lubricant Additives, Coolants and Anti-Freeze Agents (Subsidiary

Hazard) Group Standard 2006.

### **SECTION 16 – ANY OTHER RELEVANT INFORMATION**

SDS INFORMATION:

Date of SDS Preparation: 26th July 2016 Revision: 0.1

**REVISION CHANGES:** Changes to supplier information and addition of HSNO number in Section 1.

**ACRONYMS:** 

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

CAS Number Chemical Abstracts Service Registry Number

EINECS European Inventory of Existing Commercial Chemical Substances

UN Number United Nations Number

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists HSE-WEL Health and Safety Executive - Workplace Exposure Limit

IMDG International Maritime Dangerous Goods IATA International Air Transport Association

IUCLID International Uniform Chemical Information Database RTECS Registry of Toxic Effects of Chemical Substances

%W/W Percent weight for weight

OECD Organisation for Economic Co-Operation and Development

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

HAZCHEM Code Emergency action code of numbers and letters which gives information to emergency services

NOHSC National Occupational Health and Safety Commission

NICNAS National Industrial Chemicals Notification & Assessment Scheme

IMAP Inventory Multi-Tiered Assessment and Prioritisation AICS Australian Inventory of Chemical Substances

TWA Time-Weighted Average STEL Short term Exposure Limit

HSNO Hazardous Substances and New Organisms Act 1996

GHS Globally Harmonised System of Classification and Labelling of Chemicals

WHS Work Health and Safety

PPE Personal Protective Equipment.

EH40/2005 Workplace Exposure Limits

Page 10 of 10 Product: Silicone Brake Fluid

## SAFETY DATA SHEET

### SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued

#### LITERATURE REFERENCES AND SOURCES OF DATA:

**OECD Guidelines for Testing of Chemicals** 

Annex I: OECD Test Guidelines for Studies Included in SIDS

Manual for the Assessment of Chemicals Chapter 2 Data Gathering

International Toxicity Testing Guidelines

Hazardous Substance Information System - Guidance Material for Hazard Classifications

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Model Work Health and Safety Regulations.

Model Work Health and Safety Regulations - Transitional Principles

Workplace Exposure Standards for Airborne Contaminants

Australian Dangerous Goods Code 7th Edition

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]

Guidance on the Classification of Hazardous Chemicals under the WHS Regulations

Assigning a Hazardous Substance to a Group Standard

User Guide to the HSNO Thresholds and Classifications

Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances

Correlation between GHS and New Zealand HSNO Hazard Classes and Categories

**HSNO Control Regulations** 

Record of Group Standard Assignment

Labelling of Hazardous Substances Hazard and Precautionary Information

Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996

Workplace Exposure Standards and Biological Exposure Indices

NICNAS IMAP Human Health Tier II Assessment for Phosphoric acid, tributyl ester CAS Number: 126-73-8

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.