# OUTBACK HARDENED 4X4 DIESEL 10W-40 (Semi Syn)

Last updated: 10/08/2022 1:09 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
OBDSL10W40010	10L	

#### **PRODUCT BENEFITS**

**Outback Hardened 4X4 Diesel 10W-40** is a premium high performance semi synthetic SAE 10W-40, non-friction modified engine oil. It contains premium base oils and an **OUTBACK HARDENED** formulation of additives, designed to provide superior protection in the toughest of operating conditions.









#### **APPLICATION**

**Outback Hardened 4X4 Diesel 10W-40** is designed for use in modern 4, 6 & 8+ cylinder multi cam, multi valve (Including VVT), naturally aspirated, supercharged, turbocharged common rail and direct injection engines.

It is recommended for use in vehicles where SAE 10W-30 & SAE 10W-40 grade engine oils were originally recommended by the manufacturer. It can be used where API CI-4, Global DLD-2, DLD-3 or JASO DH-1 is specified in the owner's hand book. It can also be used where ACEA A3/B3, ACEA A3/B4 is recommended or where ACEA E7 is recommended prior to model year 2017. It is suitable for use in many older diesel and LPG powered vehicles requiring an engine oil meeting API CI-4, API CH-4, CG-4, CF-4 or older specifications.

It is **NOT** recommended for use in diesels fitted with a DPF (Diesel Particulate Filter) that require an ACEA "C" grade Low-Mid SAPS (Sulphated Ash, Phosphorus & Sulphur) engine oil. We recommend checking the recommendation guide for the correct grade and specification.

## **VEHICLE & FUEL TYPES**

Suitable for use in diesel engines in passenger cars, motorcycles, 4WD's, light & heavy duty commercial engines in trucks, tractors, agricultural & earthmoving equipment as well as industrial equipment such as fork lifts & stationary engines. It can be used with Diesel & Petrol/E10/LPG (Dual Fuel). Suitable for petrol and LPG engines as a mixed fleet oil and can be used in motorcycles with wet clutches.

## PRODUCT BENEFITS

- OUTBACK HARDENED additive package for ultimate engine wear protection
- EXCLUSIVE to Supercheap Auto
- Increased protection over 10W-30 grade oils
- · Reduces oil consumption and maintains oil pressure
- · Protects against corrosion, oil oxidation and engine sludge
- · Reduces wear by controlling soot deposits
- · Suitable for mixed fleets of vehicles

### **PRODUCT PERFORMANCE LEVELS**

- ACEA A3/B4 (PRIOR TO 2017)
- API CI-4/SL
- Global DLD-2

- Global DLD-3
- JASO DH-1



# **TYPICAL DATA**

Density at 15°C, kg/L	0.864
Viscosity, Kinematic, cSt at 40°C	97
Viscosity, Kinematic, cSt at 100°C	14.7
Viscosity Index	158
Cold Cranking Viscosity, cP at -25°C	6092
Ca content, Mass %	0.363
Zinc, Mass %	0.109
Phosphorus, Mass %	0.099
Sulphated Ash, Mass %	1.4
Total Base Number (TBN)	11.1