



# PENRITE



85% REDUCTION  
IN LANDFILL  
WASTE

## OUTBACK HARDENED 4X4 PETROL 10W-40 (Semi Syn)

Last updated: 11/03/2020 3:21 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
OBPET10W40001	1L	6
OBPET10W40006	6L	3

### PRODUCT BENEFITS

**Outback Hardened 4X4 Petrol 10W-40** is a premium high performance semi synthetic SAE 10W-40 engine oil. It contains premium base oils and an **OUTBACK HARDENED** formulation of additives, designed to provide superior protection in the toughest of operating conditions.



**OUTBACK  
HARDENED 4X4**

EXCLUSIVE  
TO

**SUPERCHEAP  
AUTO**

### APPLICATION

**Outback Hardened 4X4 Petrol 10W-40** is designed for use in modern 4, 6 & 8+ cylinder multi-cam, multi-valve (including VVT), naturally aspirated, supercharged & turbocharged engines.

It can be used in modern petrol and light duty diesel engines where the use of SAE 10W-30 or 10W-40 oil is specified in the owner's handbook. It may be used where ACEA A3/B3 and ACEA A3/B4 is recommended in model years prior to 2017 and where API SN and previous specifications SM (2004-10), SL (2001-04), SJ were recommended. It can also be used in older diesel engines requiring API CF or earlier specifications.

### VEHICLE & FUEL TYPES

**Outback Hardened 4X4 Petrol 10W-40** is suitable for use in passenger cars, 4WD's and light commercial vehicles. It may also be used in industrial engines, fork lifts & stationary engines. It can be used with Petrol/E10/LPG (Dual Fuel) & Diesel. It is not suitable for use in diesel vehicles fitted with a DPF (Diesel Particulate Filter) or in Motorcycles with a wet clutch.

### PRODUCT BENEFITS

- **OUTBACK HARDENED** additive package for ultimate engine wear protection
- **EXCLUSIVE** to Supercheap Auto
- Increased protection over 10W-30 grade oils
- Reduces oil consumption and maintains oil pressure
- Catalytic converter compatible.
- Ideal for light duty diesel engines
- Minimises sludge formation
- Maximises wear protection
- Reduces piston deposits

### INDUSTRY & MANUFACTURER'S SPECIFICATIONS

- ACEA A3/B4 (PRIOR TO 2017)
- API SL/CF
- API SM/CF
- API SN/CF



# PENRITE



**85% REDUCTION  
IN LANDFILL  
WASTE**

## **TYPICAL DATA**

Density at 15°C, kg/L	0.861
Viscosity, Kinematic, cSt at 40°C	96
Viscosity, Kinematic, cSt at 100°C	14.1
Viscosity Index	151
Cold Cranking Viscosity, cP at -25°C	6327
Ca content, Mass %	NIL
Zinc, Mass %	0.108
Phosphorus, Mass %	0.098
Sulphated Ash, Mass %	0.83
Total Base Number (TBN)	7.6