OUTBACK HARDENED 4X4 TRANS GEAR 75W-90 (Semi Syn)

Last updated: 02/10/2024 3:19 pm

PRODUCT CODE	PACK SIZE	CARTON QTY
OBTG75W90004	4L	4

PRODUCT BENEFITS

Outback Hardened 4X4 Semi Synthetic 75W-90 is a semi-synthetic manual gearbox & transaxle oil. It is manufactured with an **OUTBACK HARDENED** additive pack with a blend of highly refined base oils. It meets the performance requirements of API MT-1 and GL-5 as well as many manufacturers' requirements.









APPLICATION

Outback Hardened 4X4 Semi Synthetic 75W-90 is a highly versatile product that can be used in transaxles, gearboxes, transfer cases and differentials of a wide range of passenger vehicles, 4WDs, light & heavy duty commercials or where API GL-4 or GL-5 SAE 75W-90 oils are recommended. It may also be used in differentials of all types of equipment that require 80W-90 oils, including heavy duty differentials, that specify this type of oil. It can also be used in heavy duty truck and bus manual gearboxes where API GL-5 SAE 80W-90 oils are required but are not giving the desired shift characteristics. It may be used in some gearboxes made by: Hino, MAN, Mercedes-Benz, Volvo.

PRODUCT BENEFITS

- OUTBACK HARDENED additive pack
- SEMI SYNTHETIC base oils
- · Smooth shifting for the life of the oil drain
- · Enhanced oxidation stability, reducing harmful deposits.
- Excellent wear protection.
- · Protects against gear pitting.
- · Can extend transmission drain intervals compared to conventional gear oils.

PRODUCT PERFORMANCE LEVELS

- API GL-5
- API MT-1
- China National GB 13895-1992
- Mack GO-J (level)
- MAN 342 ML
- MAN 342 N
- MB 235.5.
- MB 235.6.

- MIL-L-2105D
- Volvo 1273.10
- ZF TE ML 05
- ZF TE ML 03
 ZF TE ML 07
- ZF TE ML 08
- ZF TE-ML 01
- ZF TE-ML 02



TYPICAL DATA

Colour	Amber
Density at 15°C, kg/L	0.888
Viscosity, Kinematic, cSt at 40°C	94
Viscosity, Kinematic, cSt at 100°C	16.0
Viscosity Index	162
Brookfield Viscosity, cP at -40°C	127000
Phosphorus, Mass %	0.095